



A-88C

Corrugated Bundler

Description

High performance automatic bundler is specially designed for corrugated industry. It can work with strap width 5,6,9 mm and standard arch size is W 1650 x H 500 mm; W 1250/1450 x H 500 mm as optional per request.

Easy operation as OFF-LINE or integrate with existing IN-LINE conveyor system. Joinpack 3-sides squaring machine CS1 could be integrated in front of it and complete your production-line ideally.

Features

- Mitsubishi PLC
- Safety interlock
- Looping ejector
- One piece tracking system
- Double bar with rubber press
- Smooth & high speed feeding
- Waist auto loading system
- Capable to run narrow & light strap
- Dispenser swing 90 degree for easy loading
- HMI touch screen control panel, user friendly
- High speed servo motor direct driving system
- Heavy duty knurled roller conveyor, speed adjustable

Options

- Arch size: 1450(W) x 500(H)mm / 1250(W) x 500(H)mm

Specification

Speed (straps / min)	33
Strap width (mm)	5,6,9 specified
Tension range for 5,6mm	2~30kgs
Tension range for 9mm	50kgs
Standard arch (W x H mm)	1650 x 500
Motor	Servo
Sealing method	Heating element
Table height (mm)	693~1420
Power supply	110/220/230/240V, 50/60Hz, 1PH 220/230/380/415/440V, 50/60Hz, 3PH
Power consumption (kw)	1.9
Layout dimension (L x W x Hmm)	2342 x 790 x 2049~2770

*Specification subject to change without notice



JIA-IN INDUSTRY CO., LTD.

T +886 4 2359 4966

F +886 4 2359 2449

E info@joinpack.com

www.joinpack.com

