



A-93LAR

Fully Automatic Roller Driven
With Low Table

Description

Ideal for heavy, bulky package.

Lower table height allows itself to integrate with low height conveyers.

Ideal designed to integrate by IN-LINE with other machines for general industry.

Various arch size combination and workability of different strap widths between 9 ~ 15 mm can serve all kinds of packages.

Tension range between 15~70 KGs and cycles speed 24 straps.

Available to equip with various unique options to perform advanced functions.

Features

- For PP & PET straps
- Proximity cam switch
- Instant heating system
- Heavy duty steel rollers
- Weld cooling time adjustable
- Hinged power roller driven table top
- Up-stream and down-stream interlock
- Heating temperature from 230°C ~460°C

Options

- Top press
- Looping ejector
- Auto-loading system
- Stacker light with buzzer
- Coil end strap ejecting out
- Stainless steel housing (SUS#304)

Specification

Speed (straps / min)	24
Strap width (mm)	9,12,15 specified
Tension range	15~70kgs
Roller speed (m/min)	10~40 adjustable
Standard arch (W x H mm)	850 x 600
Motor	AC
Sealing method	Heating element
Table height (mm)	440
Power supply	110/220/230/240V, 50/60Hz, 1PH 220/230/380/415/440V, 50/60Hz, 3PH
Power consumption (kw)	1.0
Layout dimension (L x W x Hmm)	1925 x 705 x 1480

*Specification subject to change without notice



JIA-IN INDUSTRY CO., LTD.

T +886 4 2359 4966

F +886 4 2359 2449

E info@joinpack.com

www.joinpack.com

